



## KRB 0560

KRB-0560 is a crimping tool for non insulated connectors 6.3 mm, 0.5 - 6mm<sup>2</sup>/250°, AWG 22-10,B/F-Crimp. Short and long handle available.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



### TECHNICAL DATA

Length: 256 mm/10.08"

Width: 22 mm/0.87"

Height: 80 mm/3.15"

Weight: 560 gr/1.23 lb

Wire size: 0.5-6 mm<sup>2</sup> / AWG 22-AWG 10

Crimp dimensions mm/mm<sup>2</sup>:

0.5 - 1.5 mm<sup>2</sup>/1.5 - 2.5 mm<sup>2</sup>/4 - 6 mm<sup>2</sup>

Crimp dimensions inch/AWG:

AWG 22 - AWG 16/AWG 16 - AWG 14/AWG 12 -

AWG 10

Connector: Uninsulated open barrel connectors

Description: For uninsulated open barrel connectors.

Life span, cycles: 50,000

[PRINT PRODUCT LEAFLET](#)

[MANUAL](#)

[CONTACT](#)

[WATCH VIDEO](#)

[SHARE](#)

[ADD TO FAVORITE](#)