



## MCT FRAME

MCT FRAME is a crimping tool frame for mobile tool die sets. Easily interchangeable crimp dies are kept together with a special pin to simplify handling. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy-access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

The part number is a reference to the frame without dies.

Following dies are available:

## TECHNICAL DATA

Length: 234 mm/9.21"  
 Width: 31 mm/1.22"  
 Height: 64 mm/2.52"  
 Weight: 460 gr/1.23 lb  
 Description: Tool frame for mobile die sets.  
 Life span, cycles: 20.000

[PRINT PRODUCT LEAFLET](#)

[MANUAL](#)

[CONTACT](#)

[WATCH VIDEO](#)

[SHARE](#)

[ADD TO FAVORITE](#)



### Mobile die set/4300-3154/AAA

Mobile die set for endsleeves 35-50 mm<sup>2</sup>/AWG 2-0.



### Mobile die set/4300-3150/AAA

Mobile die set for non insulated open barrel connectors 0.1-1 mm<sup>2</sup>/AWG 26-18.



### Mobile die set/4300-3151/AAA

Mobile die set for non insulated open barrel connectors 0.5-2.5 mm<sup>2</sup>/AWG 22-14.



### Mobile die set/4300-3146/AAA

Mobile die set for non insulated open barrel connectors 0.5-6 mm<sup>2</sup>/AWG 22-10.



### Mobile die set/4300-3128/AAA

Mobile die set for insulated connectors, 0.1-6 mm<sup>2</sup>/AWG 26-10 (green, yellow)



### Mobile die set/4300-3129/AAA

Mobile die set for insulated connectors, 0.5-2.5 mm<sup>2</sup>/AWG 22-14 (red, blue).





**Mobile die set/4300-3262/AAA**

Mobile die set for insulated heat shrink butt splice connectors, 0.32-6 mm<sup>2</sup>/AWG 22-10 (green, yellow).



**Mobile die set/4300-3258/AAA**

Mobile die set for insulated heat shrink butt splice connectors, 0.5-2.5 mm<sup>2</sup>/AWG 22-14 (red, blue).



**Mobile die set/4300-3139/AAA**

Mobile die set for non insulated connectors 4-10 mm<sup>2</sup>/AWG 12-8.



**Mobile die set/4300-3137/AAA**

Mobile die set for non insulated connectors 0.50-2.5 mm<sup>2</sup>/AWG 22-14.



**Mobile die set/4300-3142/AAA**

Mobile die set for non insulated connectors 0.5-6 mm<sup>2</sup>/AWG 22-10.



**Mobile die set/4300-3147/AAA**

Mobile die set for Turned pin connectors, 0.14-4 mm<sup>2</sup>/AWG 26-12.



**Mobile die set/4300-3148/AAA**

Mobile die set for Turned pin connectors 6-10 mm<sup>2</sup>/AWG 10-8.



**Mobile die set/4300-3136/AAA**

Mobile die set for coaxial connectors RG 58, 59, 62, 71 BNC/TNC.



**Mobile die set/4300-3141/AAA**

Mobile die set for coaxial-/Fiberoptic: ST, SC, SMA, SMB, SFR.



**Mobile die set/4300-3140/AAA**

Mobile die set for coaxial connectors: RG 174, RG 179/BNC/TNC.



**Mobile die set/4300-3138/AAA**

Mobile die set for coaxial connectors: CATV RG 6.59.



**Mobile die set/4300-3144/AAA**

Mobile die set for RJ45 connectors 8/8, 8/6, 8/4.



**Mobile die set/4300-3127/AAA**

Mobile die set for endsleeves 0.25-10 mm<sup>2</sup>/AWG 24-8.



**Mobile die set/4300-3153/AAA**

Mobile die set for endsleeves 16-25 mm<sup>2</sup>/AWG 6-4.



**Mobile die set/4300-3132/AAA**

Mobile die set for RJ11 connectors 6/6, 6/4.



