



RRB 0315L

RRB-0315L is a crimping tool for Super Seal type connectors with seal, uninsulated open barrel connectors, 0.35 - 1.5 mm²/AWG 22-16, B/F-Crimp.

- Unique "snap on" locator design for full visibility of connector and wire insertion
- Parallel action for precision and consistent crimp results
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Tool-less die closure adjustment for maintenance and calibration
- Small size makes it easy to use in confined areas
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



TECHNICAL DATA

Length: 230 mm/9.06"

Width: 22 mm/0.87"

Height: 75 mm/2.95"

Weight: 443 gr/0.98 lb

Wire size: 0.35-1.5 mm² / AWG 22-AWG 16

Crimp dimensions mm/mm²:

0.35 - 0.5/0.75 - 1.5

Crimp dimensions inch/AWG:

AWG 22 - AWG 20/AWG 20 - AWG 16

Connector: Connectors with seal, 1.5 system type.

Description:

For non insulated open barrel super seal connectors

.

Life span, cycles: 50,000

[PRINT PRODUCT LEAFLET](#)

[MANUAL](#)

[CONTACT](#)

[WATCH VIDEO](#)

[SHARE](#)

[ADD TO FAVORITE](#)