



### RRB 0315

RRB-0315 is a crimping tool for Super Seal type connectors with seal, uninsulated open barrel connectors, 0.35 - 1.5 mm<sup>2</sup>/AWG 22-16, B/F-Crimp. -

- Unique "snap on" locator design for full visibility of connector and wire insertion
- Parallel action for precision and consistent crimp results
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Tool-less die closure adjustment for maintenance and calibration
- Small size makes it easy to use in confined areas
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



#### TECHNICAL DATA

Length: 190 mm/7.48"  
Width: 21 mm/0.83"  
Height: 74 mm/2.91"  
Weight: 317 gr/0.7 lb  
Wire size: 0.35-1.5 mm<sup>2</sup> / AWG 22-AWG 16  
Crimp dimensions mm/mm<sup>2</sup>:  
0.35 - 0.5/0.75 - 1.5  
Crimp dimensions inch/AWG:  
AWG 22 - AWG 20/AWG 20 - AWG 16  
Connector: Connectors with seal, 1.5 system type.  
Description:  
For non insulated open barrel super seal connectors.  
Life span, cycles: 50,000

[PRINT PRODUCT LEAFLET](#)

[MANUAL](#)

[CONTACT](#)

[WATCH VIDEO](#)

[SHARE](#)

[ADD TO FAVORITE](#)