



SICHERUNGSRINGZANGEN CIRCLIP PLIERS

„MIG-Circlip“ SicherungsringZange für Innenringe

- zur Montage von Sicherungsringen innen (DIN 472 und DIN 984) in Bohrungen von Ø 8 - 140 mm
- Version 1: gerade Spitzen (DIN 5256 Form C)

„MIG-Circlip“ Circlip pliers for internal rings

- for fitting internal circlips (DIN 471 und DIN 983) into bores from Ø 8 - 140 mm
- Version 1: straight tips (DIN 5256 Form C)

Ref-No.	2622	3422	H H H H H H H		Ring- größe	g	DIN 5256 C
			mm	"			
56-0800	•	•	145	5 1/2	J0 8-13 mm	85	
56-1200	•	•	145	5 1/2	J1 12-25 mm	85	
56-1900	•	•	185	7	J2 19-60 mm	185	
56-4000	•	•	230	9	J3 40-100 mm	240	
56-8500	•	•	310	12 1/2	J4 85-140 mm	470	

„MIG-Circlip“ SicherungsringZange für Innenringe 90°

- zur Montage von Sicherungsringen innen (DIN 472 und DIN 984) in Bohrungen von Ø 8 - 140 mm
- Version 2: 90°gebogene Spitzen (DIN 5256 Form D)

„MIG-Circlip“ Circlip pliers for internal rings 90°

- for fitting internal circlips (DIN 471 und DIN 983) into bores from Ø 8 - 140 mm
- Version 2: 90° angled tips (DIN 5256 Form D)

Ref-No.	2622	3422	H H H H H H H		Ring- größe	g	DIN 5256 D
			mm	"			
57-0800	•	•	135	5 1/2	J01 8-13 mm	85	
57-1200	•	•	135	5 1/2	J11 12-25 mm	85	
57-1900	•	•	170	7	J21 19-60 mm	185	
57-4000	•	•	215	9	J31 40-100 mm	240	
57-8500	•	•	295	12 1/2	J41 85-140 mm	470	