



VDE-ZANGEN VDE PLIERS

„Industrie“ Wasserpumpenzange

- dauerhafte Zuverlässigkeit durch durchgestecktes Gelenk
- selbstklemmend an Rohren und Muttern für sicheres und kraftsparendes Arbeiten
- robuste Form aus dauerfestem ChromVanadium-Stahl
- unempfindlich gegen Verschmutzung besonders auch im industriellen Umfeld

„Industry“ Water pump pliers

- durable box joint design for longtime reliability
- self-locking on pipes and nuts for safe and power saving work
- robust design - hard-wearing chrome vanadium steel
- insensitive to dirt - best practice in industrial surroundings

Ref-No.	2022	20RR	3SM2	35RR	40R8 VDE	44R8 VDE	mm	"			g	
77-2400	•	•	•	•	•	•	240	9 1/2	1 1/2" / 44mm	40mm	290	330

DIN ISO 8976



- dauerhafte Zuverlässigkeit durch durchgestecktes Gelenk und scharf zupackende, zusatzgehärtete Zähne (bis 61 HRC)
- selbstklemmend an Rohren und Muttern für sicheres und kraftsparendes Arbeiten
- robuste Form aus dauerfestem ChromVanadium-Stahl
- unempfindlich gegen Verschmutzung besonders auch im Außenbereich

- durable box joint design for longtime reliability and firm gripping with add. induction hardened serration (up to 61 HRC)
- self-locking on pipes and nuts for safe and power-saving work
- robust design - hard-wearing chrome vanadium steel
- insensitive to dirt - best practice in industrial surroundings

Ref-No.	2022	2700	20RR	35RR	40R8 VDE	44R8 VDE	mm	"			g	
77-2550	•	•	•	•	•	•	250	10	1 1/2" / 40mm	36mm	315	355

DIN ISO 5749