

BAUBEDARF CONSTRUCTING PRODUCTS

Bolzenschneider

- auswechselbarer Messerkopf
- geschmiedete, robuste Messer mit zusätzlich induktiv gehärteten Schneiden, Schneidenhärte ca. 62 HRC
- kraftvoll übersetzendes Kniegelenk und Stahlrohrschenkel schlagzäh pulverbeschichtet

Bolt Cutter

- exchangeable cutter head
- forged, robust blades with additional induction hardened cutting edges, hardness of cutting edge approx. 62 HRC
- powerful transmitting toggle joint and durable, impact-resistant powder coated steel tube handles

Ref-No.	5RZO 0000 cutter head		mm		HRC*			g	
			mm	"	19	40	48	g	lb
97-1330	•	•	330	13	6	5		210	775
97-1400	•	•	400	16	7	6		210	850



NEU! NEW!
48 HRC



Bolzenschneider 48 HRC mit auswechselbarem Messerkopf

- Schneidenhärte ca. 62 HRC (aus Sonder-CV-Stahl)
- kraftvoll übersetzendes Kniegelenk und Stahlrohrschenkel schlagzäh pulverbeschichtet und ERGO-Hüllen
- leichtes Nachstellen mittels doppelter Exzentrerschrauben

Bolt cutter 48 HRC with exchangeable cutter head

- hardness of cutting edge approx. 62 HRC (special High Grade CV Tool Steel)
- powerful transmitting toggle joint and durable, impact-resistant powder coated steel tube handles with ERGO-sleeves
- easy double cam bolt adjustment

Ref-No.	5RZO 0000 cutter head		mm		HRC*			g	
			mm	"	19	40	48	g	lb
97-1460	•	•	460	18	8	7	5	420	1670
97-1620	•	•	620	24	9	8	7	770	2370
97-1780	•	•	780	30	11	9	8	1450	4570
97-1900	•	•	900	36	13	11	9	1450	4980