



WASSERPUMPENZANGEN WATER PUMP PLIERS

Rohrzange 90°

- Schwedisches Modell, Form A
- stabile Doppel-T-Trägerkonstruktion
- dauerhaft scharfe, induktiv zusatzgehärtete Zähne
- Chrom-Vanadin-Elektrostahl, geschmiedet, ölgehärtet

Pipe wrench 90°

- Swedish pattern, style A
- sturdy double T-section design
- hard-wearing sharp, add. induction hardened serration
- chrome vanadium electric steel, forged, oil-hardened

DIN ISO 5234

Ref-No.	2700	mm		"	g	g
		mm	"			
98-1100	•	325	123/4	1"	0-50 mm	800
98-1200	•	415	161/2	11/2"	0-60 mm	1300
98-1300	•	540	211/2	2"	10-80 mm	2300
98-1400	•	685	27	3"	10-105 mm	4000
98-1500	•	750	29 1/2	4"	10-125 mm	4800

Rohrzange 45°

- Schwedisches Modell, Form B
- stabile Doppel-T-Trägerkonstruktion
- dauerhaft scharfe, induktiv zusatzgehärtete Zähne
- Chrom-Vanadin-Elektrostahl, geschmiedet, ölgehärtet

Pipe wrench 45°

- Swedish pattern, style B
- sturdy double T-section design
- hard-wearing sharp, add. induction hardened serration
- chrome vanadium electric steel, forged, oil-hardened

DIN ISO 5234

Ref-No.	2700	mm		"	g	g
		mm	"			
98-2100	•	265	101/2	1/2"	0-35 mm	800
98-2200	•	335	131/4	1"	0-45 mm	1300
98-2300	•	430	17	11/2"	0-55 mm	2300
98-2400	•	555	22	2"	0-70 mm	4000
98-2500	•	700	28	3"	10-95 mm	4800