

## PK 60 ID Hydraulic crimping head 10 - 240 mm<sup>2</sup>



- ▶ Extra large crimping area due to innovative 2-stage telescopic cylinders
- ▶ Indent crimping - no changing of dies required

### Characteristics

- Closed head, flip top style, rotatable
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible results

### Technical data

Crimping force 30 - 60 kN

Stroke / opening width 40.5 mm

Crimping range copper 10 - 240 mm<sup>2</sup>

Crimping range aluminum 50 - 240 mm<sup>2</sup>

Operating pressure max. 700 bar

Length 249.5 mm

Weight approx. 2.5 kg

Item	Part No.
Hydraulic crimping head 10 - 240 mm <sup>2</sup>	<b>PK60ID</b>
Scope of supply	Part No.
Carrying bag	TT2

Suitable for	Connection material	Crimping range mm <sup>2</sup>	Crimp profile
<b>Copper tubular cable lugs and connectors</b>			
Tubular cable lugs and connectors, standard type, Tubular cable lugs for switch gear connections		10 - 240	
Tubular cable lugs and connectors for fine stranded conductors		10 - 240	
<b>Terminals, connectors and pin terminals acc. to DIN</b>			
Solderless terminals (DIN 46234) connectors and pin terminals (DIN 46230, DIN 46341)		10 - 240	
<b>Aluminum compression cable lugs and connectors</b>			
Aluminum compression cable lugs and connectors acc. to DIN		50 - 240	
<b>Aluminum/copper compression cable lugs and connectors</b>			
Aluminum/copper compression cable lugs and connectors		50 - 240	