



Crimping

Hydraulic crimping heads and crimping systems

PK 60 VP Hydraulic crimping head 10 - 240 mm²



- ▶ Suitable for crimping tubular cable lugs and connectors “standard type“ and fine and superfine stranded conductors up to 240 mm²
- ▶ The patented centring system guarantees optimum crimps every time
- ▶ No additional dies required

Characteristics

- Quad-point indent crimping and wide crimping
- Open head with quick coupling, 360° rotation when not pressurised
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible results

| Technical data | |
|--|--------------------------|
| Crimping force | 55 kN |
| Crimping range | 10 - 240 mm ² |
| Operating pressure | max. 700 bar |
| Length | 305 mm |
| Weight | 2.8 kg |
| Item | Part No. |
| Hydraulic crimping head 10 - 240 mm ² | PK60VP |
| Scope of supply | Part No. |
| Carrying bag | TT2 |

| Suitable for | Connection material | Crimping range mm ² | Crimp profile |
|--|---------------------|--------------------------------|---------------|
| Copper tubular cable lugs and connectors | | | |
| Tubular cable lugs, standard type, tubular cable lugs for switchgear connections | | 10 - 240 | |
| Connectors, standard type | | 10 - 120 | |
| Tubular cable lugs for fine stranded conductors | | 10 - 240 | |
| Connectors for fine stranded conductors | | 10 - 95 | |

PK 60 VP/FT Hydraulic crimping head 16 - 300 mm²



- ▶ Suitable for crimping tubular cable lugs and connectors “standard type“ and fine and superfine stranded conductors to 300 mm²
- ▶ The patented centring system guarantees optimum crimps every time
- ▶ Closed crimping head - ideal for utility lines construction, for example

Characteristics

- Quad-point indent crimping and wide crimping
- Closed head, flip top style, 360° rotation when not pressurised
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible results

| Technical data | |
|--|--------------------------|
| Crimping force | 55 kN |
| Crimping range | 16 - 300 mm ² |
| Operating pressure | max. 700 bar |
| Length | 315 mm |
| Weight | 2.8 kg |
| Item | Part No. |
| Hydraulic crimping head 16 - 300 mm ² | PK60VPFT |
| Scope of supply | Part No. |
| Carrying bag | TT2 |

| Suitable for | Connection material | Crimping range mm ² | Crimp profile |
|---|---------------------|--------------------------------|---------------|
| Copper tubular cable lugs and connectors | | | |
| Tubular cable lugs and connectors, standard type, tubular cable lugs for switchgear connections | | 16 - 300 | |
| Tubular cable lugs and connectors for fine stranded conductors | | 16 - 300 | |