



## RB 50 B RL-E

<b>Core drill dimensions</b>	Ø 12.0 - 50.0 mm
<b>Cutting depth</b>	50.0 mm
<b>Twist drill</b>	Ø 1.0 to 16.0 mm with quick-release chuck MT2 up to Ø 20.0 mm with MT 2 DIN 345 direct
<b>Counterboring</b>	Ø 10.0 - 40.0 mm
<b>Tapping</b>	with tapping chucks: M3 - M14 with tapping attachment M3 - M20
<b>Arbors</b>	MT2
<b>Stroke</b>	170 mm
<b>Height adjustment</b>	100 mm
<b>2-speed gearbox</b>	right / left 1. Step 100 - 250 rpm 2. Step 180 - 450 rpm
<b>Power consumption</b>	1,200 W
<b>Voltage</b>	230 V 50/60 Hz 110 V 50/60 Hz
<b>Magnetic adhesion strength</b>	16,000 N
<b>Tool force (10 mm)</b>	3,800 N
<b>Magnetic base</b>	92 x 238 mm
<b>Weight</b>	16.0 kg

<b>Motor</b>	
Right/left run	✓
Oil bath gearbox	✓
<b>Slides</b>	
Infinitely adjustable	✓
<b>Operation</b>	
Soft-touch grips	✓
Ergonomic switch keyboard	✓
<b>Magnet</b>	
Metal rings	✓
<b>Made in Germany</b>	
✓	

<b>Scope of delivery</b>	
<ul style="list-style-type: none"> <li>• Metal core drilling machine RB 50 B RL-E</li> <li>• Coolant device</li> <li>• MT2 tool holder with internal cooling</li> <li>• Quick-release chuck for twist drills</li> <li>• Carrying case</li> <li>• Drill spray</li> <li>• Chip hook</li> <li>• Seat belt</li> <li>• Operating Instructions</li> <li>• <b>incl. 1 core drill free</b></li> </ul>	



## Prod.-No.

ALFRA Rotabest® RB 50 B RL-E	230 Volt	18612
ALFRA Rotabest® RB 50 B RL-E	110 Volt	18612.110