

ALFRA ROTABEST® – V 40

V-LINE



Ø10 - 32 mm

V 40

Core drill dimensions	Ø 12.0 - 40.0 mm
Cutting depth	30.0 mm
Counterboring	Ø 10.0 - 32.0 mm
Arbors	19 mm Weldon shank
1-speed gearbox	450 rpm
Stroke	45 mm
Power consumption	900 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Magnetic adhesion strength	16,000 N
Tool force (10 mm)	2,100 N
Magnetic base	95 x 200 mm
Weight	12.5 kg

Motor	
Compact, lying	
Compact mitre gear	
Slide	
2-sided column guide	
Operation	
Space-saving - through ratchet	
Magnet	
Metal rings	✓
Performance and weight optimisation	✓
Made in Germany	✓

Scope of delivery	
<ul style="list-style-type: none"> • Metal core drilling machine V 40 • Coolant pressure bottle • Carrying case • Allen key for Weldon arbor • Seat belt • Ejector pin 6.35 x 74 mm (specially for Rotabest® V 40) • Operating instructions 	
• incl. 1 core drill free	



Prod.-No.

ALFRA Rotabest® V 40	230 Volt	18712
ALFRA Rotabest® V 40	110 Volt	18712.110