



The endurance runner:

ALFRA ROTABEST® HSS-CO-RQX Core drill WELDON

- With Weldon shank 19.0 mm, 2 driving surfaces
- Internal bore 6.35 mm
- Steel quality: Special super high speed steel, coated
- polished section: with pre- and post-cutter

Suitable on:

ALFRA Rotabest®, BDS, Bux, Ruko, Magnetor, Euroboor, Universal, Nitto, Jancy, Hougen, Magtron, Promac, Rotabroach and all other magnetic drills with Weldon shank.

Cutting depth 30 mm

Cutting depth 50 mm

Ø in mm	Prod.-No.
12.0	1902012025
13.0	1902013025
14.0	1902014025
15.0	1902015025
16.0	1902016025
17.0	1902017025
18.0	1902018025
19.0	1902019025
20.0	1902020025
21.0	1902021025
22.0	1902022025
23.0	1902023025
24.0	1902024025
25.0	1902025025
26.0	1902026025
27.0	1902027025
28.0	1902028025
29.0	1902029025
30.0	1902030025
31.0	1902031025
32.0	1902032025
33.0	1902033025
34.0	1902034025
35.0	1902035025
36.0	1902036025
37.0	1902037025
38.0	1902038025
39.0	1902039025
40.0	1902040025
41.0	1902041025
42.0	1902042025
43.0	1902043025
44.0	1902044025
45.0	1902045025
46.0	1902046025
47.0	1902047025
48.0	1902048025
49.0	1902049025
50.0	1902050025
51.0	-
52.0	-
53.0	-
54.0	-
55.0	-
56.0	-
57.0	-
58.0	-
59.0	-
60.0	-

Ø in mm	Prod.-No.
12.0	1902012050
13.0	1902013050
14.0	1902014050
15.0	1902015050
16.0	1902016050
17.0	1902017050
18.0	1902018050
19.0	1902019050
20.0	1902020050
21.0	1902021050
22.0	1902022050
23.0	1902023050
24.0	1902024050
25.0	1902025050
26.0	1902026050
27.0	1902027050
28.0	1902028050
29.0	1902029050
30.0	1902030050
31.0	1902031050
32.0	1902032050
33.0	1902033050
34.0	1902034050
35.0	1902035050
36.0	1902036050
37.0	1902037050
38.0	1902038050
39.0	1902039050
40.0	1902040050
41.0	1902041050
42.0	1902042050
43.0	1902043050
44.0	1902044050
45.0	1902045050
46.0	1902046050
47.0	1902047050
48.0	1902048050
49.0	1902049050
50.0	1902050050
51.0	1902051050
52.0	1902052050
53.0	1902053050
54.0	1902054050
55.0	1902055050
56.0	1902056050
57.0	1902057050
58.0	1902058050
59.0	1902059050
60.0	1902060050

Ejector pin 6.35 x 77 mm 1926500



Ejector pin 6.35 x 102 mm 1950500



Weldon



Heavy duty serration with pre- (1) and post-cutter (2)