

# ALFRA ROTABEST® TCT CORE DRILL WELDON RAIL CARBIDE-TIPPED

- With Weldon shank 19.0 mm
- Internal bore 6.35 mm
- For highest requirements in cutting and durability when drilling railway tracks
- Polished surface: Pre – Middle – Post cutter


**Suitable for:**  
all portable magnetic drilling machines with 19 mm Weldon shank, especially for rail drilling units from the following manufacturers:

- Cembre
- Erico
- KKT
- Dubuís
- Universal
- Magtron
- Rotabroach



Ø in mm	cutting depth 25 mm	Prod.-No.
19.0		2005019025
20.0		2005020025
21.0		2005021025
22.0		2005022025
23.0		2005023025
24.0		2005024025
25.0		2005025025
26.0		2005026025
27.5		2005027525
28.0		2005028025
30.0		2005030025
31.0		2005031025
32.0		2005032025
33.0		2005033025
34.0		2005034025
36.0		2005036025
Ejector pin 6.35 x 77 mm		1926500

Ø in mm	cutting depth 50 mm	Prod.-No.
19.0		2005019050
20.0		2005020050
21.0		2005021050
22.0		2005022050
23.0		2005023050
24.0		2005024050
25.0		2005025050
26.0		2005026050
27.5		2005027550
28.0		2005028050
30.0		2005030050
31.0		2005031050
32.0		2005032050
33.0		2005033050
34.0		2005034050
36.0		2005036050
Ejector pin 6.35 x 102 mm		1950500



**ALFRA "Chip-Breaker System"**

- 1 Pre-cutter
- 2 Middle-cutter
- 3 Post-cutter

