

Insulated cable end-sleeves to DIN, with Easy-Entry



- ▶ For fine and superfine stranded conductors, e.g. to EN 60228 Cl. 5 and 6
- ▶ Easy-Entry insulation for splice-free cable insertion
- ▶ Halogen-free

Characteristics

- Colour-coding and tube dimension to DIN 46228, part 4
- Heat resistant to 105 °C

Material

- Cu-DHP
- Synthetic material: polypropylene

Surface


- Tin-plated to protect against corrosion

Technical instructions

- Tool: see page 1.134
- You will find further information on the cable descriptions in the technical appendix, page i-6

Additional information

- * = not standardised
- *** = quantities in one bag



Nominal cross section mm ²	Part No.	Colour	Hint	Dimension mm					Weight/ 1000 pcs. ~ kg	Packing unit/ pcs
				d1	d3	l1	l2	s1		
0.5	4696	<input type="checkbox"/>		1.0	3.1	12	6	0.15	0.070	1000
	4698	<input type="checkbox"/>		1.0	3.1	14	8	0.15	0.070	1000
	GR4698	<input type="checkbox"/>	***	1.0	3.1	14	8	0.15	0.070	500
	46910	<input type="checkbox"/>		1.0	3.1	16	10	0.15	0.085	1000
0.75	4706	<input type="checkbox"/>		1.2	3.3	12	6	0.15	0.080	1000
	4708	<input type="checkbox"/>		1.2	3.3	14	8	0.15	0.080	1000
	GR4708	<input type="checkbox"/>	***	1.2	3.3	14	8	0.15	0.080	500
	47010	<input type="checkbox"/>		1.2	3.3	16	10	0.15	0.100	1000
	47012	<input type="checkbox"/>		1.2	3.3	18	12	0.15	0.105	1000
1	4716	<input type="checkbox"/>		1.4	3.5	12	6	0.15	0.090	1000
	4718	<input type="checkbox"/>		1.4	3.5	14	8	0.15	0.100	1000
	GR4718	<input type="checkbox"/>	***	1.4	3.5	14	8	0.15	0.100	500
	47110	<input type="checkbox"/>		1.4	3.5	16	10	0.15	0.120	1000
	47112	<input type="checkbox"/>		1.4	3.5	18	12	0.15	0.125	1000
1.5	4726	<input type="checkbox"/>	*	1.7	4.0	12	6	0.15	0.105	1000
	4728	<input type="checkbox"/>		1.7	4.0	14	8	0.15	0.110	1000
	GR4728	<input type="checkbox"/>	***	1.7	4.0	14	8	0.15	0.110	500
	47210	<input type="checkbox"/>		1.7	4.0	16	10	0.15	0.130	1000
	47212	<input type="checkbox"/>		1.7	4.0	18	12	0.15	0.150	1000
	47218	<input type="checkbox"/>		1.7	4.0	24	18	0.15	0.190	1000
2.5	4738	<input type="checkbox"/>		2.2	4.7	14	8	0.15	0.150	1000
	GR4738	<input type="checkbox"/>	***	2.2	4.7	14	8	0.15	0.150	500
	47312	<input type="checkbox"/>		2.2	4.7	18	12	0.15	0.200	1000
	47318	<input type="checkbox"/>		2.2	4.7	24	18	0.15	0.250	1000
4	47410	<input type="checkbox"/>		2.8	5.4	17	10	0.20	0.210	100
	47412	<input type="checkbox"/>		2.8	5.4	20	12	0.20	0.250	100
	47418	<input type="checkbox"/>		2.8	5.4	26	18	0.20	0.320	100
6	47512	<input type="checkbox"/>		3.5	6.9	20	12	0.20	0.350	100
	47518	<input type="checkbox"/>		3.5	6.9	26	18	0.20	0.460	100
10	47612	<input type="checkbox"/>		4.5	8.4	22	12	0.20	0.450	100
	47618	<input type="checkbox"/>		4.5	8.4	28	18	0.20	0.650	100

See next page