



Angled tubular cable lugs, Cu, 90° and 45° angled, F-series

Nominal cross section mm ²	Size of bolt dia.	Part No.	Dimension mm							Weight/ 100 pcs. ~ kg	Packing unit/pcs
			d1	a	b	d2	d4	c1	l3		
70	M8	747F8	13.0	25	25	8.5	17.0	10.00	15.0	4.83	25
	M10	747F10	13.0	25	25	10.5	17.0	12.00	16.0	5.18	25
	M12	747F12	13.0	25	25	13.0	17.0	13.00	17.5	5.16	25
	M14	747F14	13.0	25	25	15.0	17.0	14.50	19.0	5.38	25
	M16	747F16	13.0	25	25	17.0	17.0	16.00	15.0	6.50	25
95	M8	748F8	14.5	26	28	8.5	19.0	12.00	12.0	6.66	25
	M10	748F10	14.5	26	28	10.5	19.0	12.00	15.0	6.04	25
	M12	748F12	14.5	26	28	13.0	19.0	13.00	16.0	6.58	25
	M14	748F14	14.5	26	28	15.0	19.0	14.50	17.5	7.24	25
	M16	748F16	14.5	26	28	17.0	19.0	16.00	19.0	7.34	25
120	M10	749F10	16.2	30	30	10.5	21.0	14.00	14.0	8.76	10
	M12	749F12	16.2	30	30	13.0	21.0	15.00	18.0	8.76	10
	M14	749F14	16.2	30	30	15.0	21.0	15.00	18.0	9.15	10
	M16	749F16	16.2	30	30	17.0	21.0	16.00	19.0	8.54	10
150	M10	750F10	18.0	32	34	10.5	23.0	15.00	19.0	11.54	10
	M12	750F12	18.0	32	34	13.0	23.0	16.00	21.0	11.58	10
	M14	750F14	18.0	32	34	15.0	23.0	18.00	22.0	11.90	10
	M16	750F16	18.0	32	34	17.0	23.0	19.00	23.0	11.80	10
	M20	750F20	18.0	32	40	21.0	23.0	21.00	23.0	12.00	10
185	M12	751F12	20.6	35	39	13.0	26.0	21.50	22.0	16.36	10
	M14	751F14	20.6	35	39	15.0	26.0	21.50	22.0	16.20	10
	M16	751F16	20.6	35	39	17.0	26.0	21.50	22.0	15.36	10
	M20	751F20	20.6	35	39	21.0	26.0	21.50	22.0	15.80	10
240	M16	752F16	23.1	44	41	17.0	28.0	19.00	20.0	17.80	5