

ALFRA SPLIT HOLE PUNCHER TRICUT+®

Ø in mm	Max. Material thickness in mm (VA)	Size Metric	Size PG	Size Inch	Size Conduit & Pipe Size				
						Punches and dies, draw bolt with ball bearing	Punches and dies	matching draw bolt	matching draw bolt with ball bearing

Split hole puncher TriCut+® – for sheet steel (S235) and stainless steel (VA)

							Prod.-No.			
15.2	2.0	-	9	-	0.598	-	01465	01600	02007	01342
16.2	2.0	M 16	-	-	0.638	-	01466	01656		
18.6	2.0	-	11	-	0.732	-	01467	01603		
20.4	2.0	M 20	13	-	0.803	-	01468	01606		
22.5	2.0	-	16	7/8"	0.886	1/2"	01469	01609		
25.4	2.5	M 25	-	1"	1.000	-	01470	01659		
28.3	2.5	-	21	-	1.114	3/4"	01471	01612	02002	01340
30.5	2.5	-	-	1-7/32"	1.201	-	01472	01615		
32.5	2.5	M 32	-	-	1.280	-	01473	01662		
34.6	2.5	-	-	1-11/32"	1.362	1"	01474	01618		
37.0	2.5	-	29	-	1.457	-	01475	01621		
40.5	2.5	M 40	-	-	1.594	-	01476	01665		
43.2	2.5	-	-	1-11/16"	1.701	1 1/4"	01477	01624		01341
47.0	2.5	-	36	-	1.850	-	01478	01627		
49.6	2.5	-	-	1-15/16"	1.953	1 1/2"	01479	01630		
50.5	2.5	M 50	-	-	1.988	-	01480	01668		
54.0	2.5	-	42	2-1/8"	2.126	-	01481	01633		
60.0	2.5	-	48	-	2.362	-	01482	01636		
61.5	2.5	-	-	2-3/8"	2.421	2"	01483	01640		
63.5	2.5	M 63	-	2-1/2"	2.500	-	01484	01671		