

MAGNETIC CLAMP TMC 300 R

R With prism for pipes and curved surfaces
Lifts pipes from 25 mm (1") to 200 mm (7-7/8") in diameter

- 1** Only 1.1 kg (2.4 lbs) dead weight
- 2** Max. Breakaway force: 300 kg (660 lbs)
- 3** Easy one-handed operation



MADE IN GERMANY
US Patent No. 8,350,663 B1

- Excellent holding force on pipes from 25 mm (1") to 200 mm (7-7/8") in diameter
- Outstanding performance on thin-walled materials (operable from just 1 mm; 1/32")
- The specially aligned magnetic field (patented) makes up to approx. 15 mm to the outside of the magnet (9/16") possible
- Wear-resistant magnetic contact area made of hardened steel with TiN-coating preventing damages and guaranteeing a long lifetime

Technical data TMC 300 R:

- Dead weight: 1.1 kg (2.4 lbs)
- Breakaway force: > 300 kg (660 lbs) on 6 mm (1/4") steel S235
- Max. load-bearing capacity with round pipes: 20 - 50 % of the load-bearing capacity on flat material (see TMC 300), depending on pipe diameter and material thickness
- Length: 82.5 mm (3-1/4"); width: 80 mm (3-1/8"); height: 32.5 mm (1-1/4")
(incl. lever: length 190 mm; 7-1/2", width 124 mm; 4-7/8")

Prod.-No.

ALFRA TMC 300 R

41100.R