

MAGNETIC CLAMP TMC 300

*Our “l ittle one” with a wide range of applications is t he
per fect magnetic base for your pr ojects*

- 1 Only 1 kg (2.2 lbs) dead weight
- 2 Up to 300 kg (660 lbs) load-bearing capacity (vertically)
- 3 Easy one-handed operation



- Excellent holding force up to 300 kg (660 lbs) – even on a steel plate with 6 mm (1/4") thickness only
- User-friendly one-handed operation thanks to ergonomic activation lever
- Connection threads (M5 and M6) on the top and the sides of the TMC 300 allow for the easy attachment of handling accessories such as cutting guides, angle side plates, handles, and much more
- Ideal tool to ease your work, e.g. during levelling of plates, platform construction, fixation, or any kind of clamping technique!
- The specially aligned magnetic field (patented) makes up to approx. 15 mm to the outside of the magnet (9/16") possible
- Wear-resistant magnetic contact area made of hardened steel with TiN-coating preventing damages and guaranteeing a long lifetime
- Exceptional shear force for better hold, especially during vertical applications

Technical data TMC 300:

- Dead weight: 1 kg (2.2 lbs)
- Breakaway force: > 300 kg (660 lbs) on 6 mm (1/4") steel S235
- Length: 82.5 mm (3-1/4"); width: 80 mm (3-1/8"); height: 32.5 mm (1-1/4")
(incl. lever: length 190 mm; 7-1/2", width 124 mm; 4-7/8")



Prod.-No.

ALFRA TMC 300

41100